

DIGITAL PROJECTOR | MW712




Features

- Native WXGA (1280x800) Resolution
- 3200 ANSI Lumens, 10000:1 Contrast Ratio
- 10W Speaker, Smart Eco Mode
- LAN Control, HDMI x 1, Instant Restart
- DLP 3D Ready, Long lamp life

Top / Front View



Input and Output Terminals



- | | |
|-------------------------------|-----------------|
| 1 USB | 7 Audio Out |
| 2 HDMI | 8 Audio In R/L |
| 3 S-Video/Video | 9 LAN |
| 4 Computer In-1/Computer In-2 | 10 Monitor-Out |
| 5 RS232 | 11 Security Bar |
| 6 Audio In-1/Audio In-2 | |

Specifications

Projection System	DLP
Native Resolution	WXGA(1280 x 800)
Brightness	3200AL
Contrast Ratio	10000:1
Display Color	1.07 Billion Colors
Lens	F=2.55-3.06, f=21-25.6mm
Aspect Ratio	Native 16:10 (5 aspect ratio selectable)
Throw Ratio	1.46-1.60 (62.25" @6.56ft)
Image Size (Diagonal)	30"~300"
Zoom Ratio	1.2:1
Lamp Type	230W
Lamp(Normal/Economic/SmartEco Mode)*	3500/5000/6500 hours
Keystone Adjustment	Manual, Vertical +/- 40 degrees
Projection Offset	120% ±5%
Resolution Support	VGA(640 x 480) to UXGA(1600 x 1200)
Horizontal Frequency	31K~102KHz
Vertical Scan Rate	23~120Hz
Compatibility	HDTV Compatibility: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p Video Compatibility: NTSC, PAL, SECAM 3D Compatibility: PC: 120Hz Frame Sequential 3D for resolutions up to WXGA, PC: 60Hz Top-bottom 3D for resolutions up to SXGA+ Video: 60Hz Frame Sequential 3D for resolutions up to 480i
Interface	Computer in (D-sub 15pin) x 2(Share with component) Monitor out (D-sub 15pin) x 1 HDMI(v1.3) x 1 Composite Video in (RCA) x 1 S-Video in (Mini DIN 4pin) x 1 Audio in (Mini Jack) x 2 Audio L/R in (RCA) x 2 Audio out (Mini Jack) x 1 Speaker 10W x 1 LAN (RJ45) x 1 USB (Type B) x1 (Download & page/down) RS232 (DB-9pin) x 1
Dimensions(W x H x D)	11.89 x 4.88 x 9.16 inches (302x124x232.7 mm)
Weight	5.39lbs (2.45kg)
Power Supply	AC100 to 240 V, 50 to 60 Hz
Power Consumption	285W(typical), Standby<1W
Audible Noise	29/27 dBA (Normal/Economic mode)
On-Screen Display Languages	Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/ Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages)
Picture Modes	Dynamic/Presentation/sRGB/Cinema/User 1/User 2
Accessories (Standard)	Remote Control w/ Battery, Power Cord (by region), User Manual CD, Quick Start Guide, Warranty Card (by region), VGA(D-sub 15pin) Cable
Accessories (Optional)	Spare Lamp Kit P/N: 5J.J4R05.001 Ceiling Mount P/N: 5J.J2K01.001 3D Glasses P/N: 5J.J0T14.011 Carry Bag P/N: 5J.J2V09.001
Limited Warranty	3-Years Parts/Labor / 1-Year or 2000 hours of lamp life

*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

MW712 01-04-12-BQus



BenQ America Corp.
15375 Barranca Parkway, Suite A-205, Irvine, CA 92618 ☎ Tel: (949) 255-9500 🌐 www.BenQ.us


BenQ is a registered trademark of BenQ Corp. DLP® is a registered trademark of Texas Instruments. All rights reserved. Corporate and trademarks are the property of their respective companies. Specifications subject to change without notice.



Enjoyment Matters


MW712 Digital Projector

Distance Chart



		Screen size		Distance from screen (mm)			Vertical offset (mm)	
		Diagonal	W	H	Min length	Average		Max length
Inch	mm	(mm)	(mm)	(max. zoom)		(min. zoom)		
30	762	646	403	1018	1127	1235	61	
40	1016	861	538	1273	1420	1567	83	
50	1270	1077	673	1564	1731	1897	105	
60	1524	1292	807	1871	2047	2223	126	
80	2032	1723	1077	2435	2658	2881	164	
100	2540	2153	1346	3014	3276	3538	205	
120	3048	2584	1615	3594	3894	4194	251	
150	3810	3230	2019	4465	4823	5180	313	
200	5080	4307	2692	5916	6369	6822	416	
220	5588	4738	2961	6496	6987	7478	457	
250	6350	5384	3365	7367	7916	8464	521	
300	7620	6461	4038	8818	9462	10106	624	

Wall/Ceiling Mount Chart



Unit: inch

Dimensions

